

PRODUCT DATA SHEET

U92/1E M White

100110

| | | | |
|---|--|---|--------------------------|
| Thickness (nominal) | .6 mm | / | 0.023 inch |
| Weight | .6 Kg/m ² | / | 0.12 lbs/ft ² |
| Maximum Width | 3200 mm | / | 126 inch |
| Minimum Pulley or Knife Edge Diameter (With the recommended joint) With the recommended joint & reverse flex, Overlap joint or Fasteners | 8 mm | / | 0.31 inch |
| | 16 mm | / | 0.63 inch |
| Load for 1% Extension | 3 daN/cm | / | 17 lbs/inch |
| Standard Tension | 0.5 % | | |
| Continuous Operating Temperature range | -30 ^o to +80 ^o C / -22 ^o to +176 ^o F | | |
| Conveying Surface: | | | |
| Material | Polyurethane | | |
| Feature | Matt | | |
| Color | White | | |
| Underside: | | | |
| Material | Polyester | | |
| Feature | PU Impregnation | | |
| Color | White | | |
| Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum) | 0.15 | | |
| Belt Construction Features | 1 Ply monofilament – cover one side | | |
| Recommended Jointing System: | Alternative Splices: | | |
| Single Finger | Lace | | |
| Anti-Static | No | | |
| FDA Approved | Yes | | |

