



UNIVERSAL BELTING RESOURCE

"Working Through Distribution"

1-800-928-9995

customers@ubelting.com

# PRODUCT DATA SHEET

## U92/2E Matt White

100210

Thickness (nominal)	1.30 mm / 0.051 inch
---------------------	----------------------

Weight	1.4 Kg/m <sup>2</sup> / 0.29 lbs/ft <sup>2</sup>
--------	--

Maximum Width	3200 mm / 126 inch
---------------	--------------------

Minimum Pulley or Knife Edge Diameter (With The Recommended Joint)	8 mm / 0.31 inch
With The Recommended Joint & Reverse Flex Diameter Overlap joint or Fasteners	25 mm / 0.98 inch

Load for 1% Extension	7 N/mm / 40 lbs/inch
-----------------------	----------------------

Standard Tension	0.5 %
------------------	-------

Continuous Operating Temperature Range (Product Temp.)	-20 <sup>o</sup> to +100 <sup>o</sup> C / -4 <sup>o</sup> to +212 <sup>o</sup> F
--	--

Conveying Surface:	
Material	Polyurethane, approx. 0.2mm
Feature	Matt
Color	White
Hardness	92A

Underside:	
Material	Polyester
Feature	PU Impregnation
Color	White
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.25

Recommended Jointing System: Finger Splice	Alternative Splices: Finger over Finger Finger over Lap Step Splice Lace
---	--

Anti-Static	No
-------------	----

FDA Approved	Yes
--------------	-----

USDA Approved	No
---------------	----

Belt Construction Features	2 Ply Monofilament - Cover One Side General Conveying Belt
----------------------------	---