



**UNIVERSAL BELTING RESOURCE**  
 "Working Through Distribution"

1-800-928-9995  
 customers@ubelting.com

# PRODUCT DATA SHEET

## U92/2E AM Plus Matt Blue

**100212**

Thickness (nominal)	1.30 mm	/	0.051 inch
---------------------	---------	---	------------

Weight	1.4 Kg/m <sup>2</sup>	/	0.29 lbs/ft <sup>2</sup>
--------	-----------------------	---	--------------------------

Maximum Width	3200 mm	/	126 inch
---------------	---------	---	----------

Minimum Pulley or Knife Edge Diameter (With The Recommended Joint)	8 mm	/	0.31 inch
With The Recommended Joint & Reverse Flex Diameter Overlap joint or Fasteners	25 mm	/	0.98 inch

Load for 1% Extension	7 N/mm	/	40 lbs/inch
-----------------------	--------	---	-------------

Standard Tension	0.5 %		
------------------	-------	--	--

Continuous Operating Temperature Range (Product Temp.)	-20 <sup>o</sup> to +100 <sup>o</sup> C	/	-4 <sup>o</sup> to +212 <sup>o</sup> F
--	---	---	--

Conveying Surface:			
Material	Anti-Microbial Polyurethane, approx. 0.2mm		
Feature	Matt		
Color	Blue		
Hardness	92A		

Underside:			
Material	Polyester		
Feature	PU Impregnation		
Color	White		
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.25		

Recommended Jointing System: Finger Splice	Alternative Splices: Finger over Finger Finger over Lap Step Splice Lace
---	--

Anti-Static	No
-------------	----

FDA Approved	Yes
--------------	-----

USDA Approved	No
---------------	----

Belt Construction Features	2 Ply Monofilament - Cover One Side with Anti-Microbial Urethane. General Conveying Belt
----------------------------	--