

# PRODUCT DATA SHEET

## U92 XH/2E-AS G Clear

100250

Thickness (nominal)	2.0 mm	/	0.079 inch
Weight	2.2 Kg/m <sup>2</sup>	/	0.45 lbs/ft <sup>2</sup>
Maximum Width	3200 mm	/	126 inch
Minimum Pulley or Knife Edge Diameter (With the recommended joint) With the recommended joint & reverse flex, Overlap joint or Fasteners	40 mm	/	1.57 inch
	60 mm	/	2.36 inch
Load for 1% Extension	7 daN/cm	/	40 lbs/inch
Standard Tension	0.5 %		
Continuous Operating Temperature range	-20 <sup>o</sup> to +100 <sup>o</sup> C / -4 <sup>o</sup> to +212 <sup>o</sup> F		
Conveying Surface:			
Material	Polyurethane		
Feature	Gloss		
Color	Clear		
Underside:			
Material	Polyester		
Feature	PU Impregnation		
Color	Clear		
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.15		
Belt Construction Features	2 Ply monofilament – cover one side		
<b>Recommended Jointing System:</b>	<b>Alternative Splices:</b>		
Single Finger	Finger over Step Lace Spiral lace		
Anti-Static	Yes		
FDA Approved	Yes		

