



UNIVERSAL BELTING RESOURCE
 "Working Through Distribution"

1-800-928-9995
 customers@ubelting.com

PRODUCT DATA SHEET

U92/2E-AS Matt Clear

100254

Thickness (nominal)	1.80 mm	/	0.071 inch
---------------------	---------	---	------------

Weight	2.0 Kg/m ²	/	0.41 lbs/ft ²
--------	-----------------------	---	--------------------------

Maximum Width	3200 mm	/	126 inch
---------------	---------	---	----------

Minimum Pulley or Knife Edge Diameter (With The Recommended Joint)	30 mm	/	1.18 inch
With The Recommended Joint & Reverse Flex Diameter Overlap joint or Fasteners	50 mm	/	1.97 inch

Load for 1% Extension	7 N/mm	/	40 lbs/inch
-----------------------	--------	---	-------------

Standard Tension	0.5 %		
------------------	-------	--	--

Continuous Operating Temperature Range (Product Temp.)	-20 ^o to +100 ^o C	/	-4 ^o to +212 ^o F
--	---	---	--

Conveying Surface:			
Material	Polyurethane, approx. 0.5mm		
Feature	Matt		
Color	Transparent		
Hardness	92A		

Underside:			
Material	Polyester		
Feature	PU Impregnation		
Color	White		
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.25		

Recommended Jointing System: Finger Splice	Alternative Splices: Finger over Lap Finger over Finger Step Splice Lace
---	--

Anti-Static	Yes
-------------	-----

FDA Approved	Yes
--------------	-----

USDA Approved	No
---------------	----

Belt Construction Features	2 Ply Monofilament with matt finish top cover having excellent abrasion and cut resistance. Excellent for make up tables, metal parts conveying, etc.
----------------------------	---