



UNIVERSAL BELTING RESOURCE
 "Working Through Distribution"

1-800-928-9995
 customers@ubelting.com

PRODUCT DATA SHEET

U92 XH/2EX AS Clear Gloss

100257

Thickness (nominal)	3.70 mm / 0.146 inch
---------------------	----------------------

Weight	4.20 Kg/m ² / 0.86 lbs/ft ²
--------	---

Maximum Width	3000 mm / 118 inch
---------------	--------------------

Minimum Pulley or Knife Edge Diameter (With The Recommended Joint)	100 mm / 3.94 inch
With The Recommended Joint & Reverse Flex Diameter Overlap joint or Fasteners	125 mm / 4.92 inch

Load for 1% Extension	8 N/mm / 45 lbs/inch
-----------------------	----------------------

Standard Tension	0.5 %
------------------	-------

Continuous Operating Temperature Range (Product Temp.)	-20 ^o to +100 ^o C / -4 ^o to +212 ^o F
--	--

Conveying Surface:	
Material	Polyurethane, approx. 1.5mm
Feature	Gloss
Color	Transparent
Hardness	92A

Underside:	
Material	Polyester
Feature	Impregnated
Color	Clear
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.25

Recommended Jointing System: Finger Splice	Alternative Splices: Finger over Lap Finger over Finger Step Splice Lace
---	--

Anti-Static	Yes
-------------	-----

FDA Approved	Yes
--------------	-----

USDA Approved	No
---------------	----

Belt Construction Features	2 Ply Monofilament - Cover One Side Heavy Cover 2 Ply, Great For Stamping Applications
----------------------------	---