



UNIVERSAL BELTING RESOURCE
 "Working Through Distribution"

1-800-928-9995
 customers@ubelting.com

PRODUCT DATA SHEET

U0/1E Green

100605

Thickness (nominal)	.5 mm	/	0.020 inch
Weight	.3 Kg/m ²	/	0.05 lbs/ft ²
Maximum Width	2200 mm	/	86 inch
Minimum Pulley or Knife Edge Diameter (With the recommended joint) With the recommended joint & reverse flex, Overlap joint or Fasteners	10 mm	/	0.39 inch
	10 mm	/	0.39 inch
Load for 1% Extension	3 daN/cm	/	17 lbs/inch
Standard Tension	0.5 %		
Continuous Operating Temperature range	-40 ^o to +100 ^o C / -20 ^o to +212 ^o F		
Conveying Surface:			
Material	Polyester		
Feature	PU Impregnation		
Color	Green		
Underside:			
Material	Polyester		
Feature	PU Impregnation		
Color	Green		
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.15		
Belt Construction Features	1 Ply monofilament – impregnated		
Recommended Jointing System: Single Finger	Alternative Splices:		
Anti-Static	No		
FDA Approved	Yes		

