



UNIVERSAL BELTING RESOURCE
 "Working Through Distribution"

1-800-928-9995
 customers@ubelting.com

PRODUCT DATA SHEET

U0/2E-AS Gray

100715

Thickness (nominal)	1.45 mm / 0.057 inch
---------------------	----------------------

Weight	1.4 Kg/m ² / 0.29 lbs/ft ²
--------	--

Maximum Width	3200 mm / 126 inch
---------------	--------------------

Minimum Pulley or Knife Edge Diameter (With The Recommended Joint)	25 mm / 0.98 inch
With The Recommended Joint & Reverse Flex Diameter Overlap joint or Fasteners	40 mm / 1.57 inch

Load for 1% Extension	10 N/mm / 57 lbs/inch
-----------------------	-----------------------

Standard Tension	0.5 %
------------------	-------

Continuous Operating Temperature Range (Product Temp.)	-20 ^o to +100 ^o C / -4 ^o to +212 ^o F
--	--

Conveying Surface:	
Material	Polyester Fabric
Feature	PU Impregnation
Color	Gray
Hardness	N/A

Underside:	
Material	Polyester Fabric
Feature	PU Impregnation
Color	Gray
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.25

Recommended Jointing System: Finger Splice	Alternative Splices: Finger over Lap Finger over Finger Step Splice Lace
---	--

Anti-Static	Yes
-------------	-----

FDA Approved	Yes
--------------	-----

USDA Approved	No
---------------	----

Belt Construction Features	High Strength 2 Ply Monofilament - Impregnated Fabric on Both Sides, Good for Accumulation.
----------------------------	---