



**UNIVERSAL BELTING RESOURCE**  
 "Working Through Distribution"

1-800-928-9995  
 customers@ubelting.com

# PRODUCT DATA SHEET

## U0/2E-AS G Clear

100720

Thickness (nominal)	.95 mm	/	0.037 inch
Weight	.90 Kg/m <sup>2</sup>	/	0.18 lbs/ft <sup>2</sup>
Maximum Width	3200 mm	/	126 inch
Minimum Pulley or Knife Edge Diameter (With the recommended joint) With the recommended joint & reverse flex, Overlap joint or Fasteners contact factory.	6 mm	/	0.236 inch
	8 mm	/	0.315 inch
Load for 1% Extension	5 daN/cm	/	29 lbs/inch
Standard Tension	0.5 %		
Continuous Operating Temperature range	-20 <sup>o</sup> to +100 <sup>o</sup> C / -4 <sup>o</sup> to +212 <sup>o</sup> F		
Conveying Surface:			
Material	Polyester Fabric		
Feature	PU impregnation		
Color	Clear		
Underside:			
Material	Polyester fabric		
Feature	PU impregnation		
Color	Clear		
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.15		
Belt Construction Features	2 Ply monofilament bare x bare		
<b>Recommended Jointing System:</b>	<b>Alternative Splices:</b>		
Single Finger	Lace Spiral Lace		
Anti-Static	Yes		
FDA Approved	Yes		

