



UNIVERSAL BELTING RESOURCE
 "Working Through Distribution"

1-800-928-9995
 customers@ubelting.com

PRODUCT DATA SHEET

U85/2ES Matt White

110200

Thickness (nominal)	1.65 mm	/	0.065 inch
---------------------	---------	---	------------

Weight	1.8 Kg/m ²	/	0.37 lbs/ft ²
--------	-----------------------	---	--------------------------

Maximum Width	3200 mm	/	126 inch
---------------	---------	---	----------

Minimum Pulley or Knife Edge Diameter (With The Recommended Joint)	10 mm	/	0.39 inch
With The Recommended Joint & Reverse Flex Diameter Overlap joint or Fasteners	25 mm	/	0.98 inch

Load for 1% Extension	6 N/mm	/	34 lbs/inch
-----------------------	--------	---	-------------

Standard Tension	0.5 %
------------------	-------

Continuous Operating Temperature Range (Product Temp.)	-30 ^o to +80 ^o C	/	-22 ^o to +176 ^o F
--	--	---	---

Conveying Surface:	
Material	Polyurethane, approx. 0.2mm
Feature	Matt
Color	White
Hardness	85A

Underside:	
Material	Polyester Spun
Feature	PU Impregnation
Color	White
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.25

Recommended Jointing System: Finger Splice	Alternative Splices: Finger over Lap Finger over Finger Step Splice Lace
---	--

Anti-Static	No
-------------	----

FDA Approved	Yes
--------------	-----

USDA Approved	No
---------------	----

Belt Construction Features	2 Ply Spun Fabric - Cover one Side with PU Inner Layer. Suitable for Curve Belts, Metal Detectors And General Bakery and Confectionary Lines.
----------------------------	---