



UNIVERSAL BELTING RESOURCE
 "Working Through Distribution"

1-800-928-9995
 customers@ubelting.com

PRODUCT DATA SHEET

U-SI/2ES UR Matt White

110210

Thickness (nominal)	1.60 mm / 0.063 inch
---------------------	----------------------

Weight	1.8 Kg/m ² / 0.37 lbs/ft ²
--------	--

Maximum Width	3200 mm / 126 inch
---------------	--------------------

Minimum Pulley or Knife Edge Diameter (With The Recommended Joint)	10 mm / 0.39 inch
With The Recommended Joint & Reverse Flex Diameter Overlap joint or Fasteners	25 mm / 0.98 inch

Load for 1% Extension	8 N/mm / 45 lbs/inch
-----------------------	----------------------

Standard Tension	0.5 %
------------------	-------

Continuous Operating Temperature Range (Product Temp.)	-20 ^o to +100 ^o C / -4 ^o to +212 ^o F
--	--

Conveying Surface:	
Material	Polyurethane / Silicone Blend, approx. 0.2mm
Feature	Matt
Color	White
Hardness	85A

Underside:	
Material	Polyester Spun
Feature	PU Impregnation
Color	White
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.25

Recommended Jointing System: Finger Splice	Alternative Splices: Finger over Lap Finger over Finger Step Splice Lace
---	--

Anti-Static	No
-------------	----

FDA Approved	Yes
--------------	-----

USDA Approved	No
---------------	----

Belt Construction Features	2 Ply Spun Fabric - High Release Cover one Side with PU Inner Layer. Suitable for Curve Belts, Metal Detectors, Sticky Bakery Applications and Confectionary Lines. Excellent For Use With Scrapers.
----------------------------	--