

PRODUCT DATA SHEET

U0/2ES White Rib

110300

| | | | |
|--|--|---|--------------------------|
| Thickness (nominal) | 1.7 mm | / | 0.067 inch |
| Weight | 1.4 Kg/m ² | / | 0.29 lbs/ft ² |
| Maximum Width | 3200 mm | / | 126 inch |
| Minimum Pulley or Knife Edge Diameter (With the recommended joint) | 12 mm | / | 0.47 inch |
| With the recommended joint & reverse flex, Overlap joint or Fasteners | 12 mm | / | 0.47 inch |
| Load for 1% Extension | 5 daN/cm | / | 29 lbs/inch |
| Standard Tension | 0.5 % | | |
| Continuous Operating Temperature range | -30° to +80° C / -22° to +176° F | | |
| Conveying Surface: | | | |
| Material | Polyester spun fabric | | |
| Feature | Bare | | |
| Color | White | | |
| Underside: | | | |
| Material | Polyester spun fabric | | |
| Feature | Bare | | |
| Color | White | | |
| Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum) | 0.15 | | |
| Belt Construction Features | 2 Ply spun fabric with rough structure | | |
| Recommended Jointing System: | Alternative Splices: | | |
| Finger Over Lap | Single Finger | | |
| | Lace | | |
| | Spiral Lace | | |
| Anti-Static | No | | |

