

# PRODUCT DATA SHEET

**U0/2ES-0 White**

**110305**

Thickness (nominal)	1.4 mm	/	0.055 inch
Weight	1.2 Kg/m <sup>2</sup>	/	0.25 lbs/ft <sup>2</sup>
Maximum Width	3200 mm	/	126 inch
Minimum Pulley or Knife Edge Diameter (With the recommended joint)	10 mm	/	0.39 inch
With the recommended joint & reverse flex, Overlap joint or Fasteners	10 mm	/	0.39 inch
Load for 1% Extension	6 daN/cm	/	34 lbs/inch
Standard Tension	0.5 %		
Continuous Operating Temperature range	-30 <sup>o</sup> to +80 <sup>o</sup> C / -22 <sup>o</sup> to +176 <sup>o</sup> F		
Conveying Surface:			
Material	Polyester spun fabric		
Feature	PU Impregnation		
Color	White		
Underside:			
Material	Polyester spun fabric		
Feature	Bare		
Color	White		
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.15		
Belt Construction Features	2 Ply spun fabric Impregnated fabric top side		
Recommended Jointing System:	Alternative Splices:		
Single Finger	Finger over lap Lace Spiral Lace		
Anti-Static	No		
FDA Approved	Yes		

