



UNIVERSAL BELTING RESOURCE
 "Working Through Distribution"

1-800-928-9995
 customers@ubelting.com

PRODUCT DATA SHEET

02/ES-0 White Rib

110315

Thickness (nominal)	2.0 mm	/	0.078 inch
Weight	1.9 Kg/m ²	/	0.39 lbs/ft ²
Maximum Width	3200 mm	/	126 inch
Minimum Pulley or Knife Edge Diameter (With the recommended joint) With the recommended joint & reverse flex, Overlap joint or Fasteners	10 mm	/	0.39 inch
	24 mm	/	0.94 inch
Load for 1% Extension	5 daN/mm	/	29 lbs/inch
Standard Tension	0.5 %		
Continuous Operating Temperature range	-30° to +100° C / -22° to +212° F		
Conveying Surface:			
Material	Polyester spun fabric		
Feature	Bare		
Color	White		
Underside:			
Material	Polyester fabric		
Feature	Bare		
Color	White		
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.25		
Belt Construction Features	2 Ply monofilament with spun rough structure		
Recommended Jointing System: Single Finger	Alternative Spices: Lace Spiral lace		
Anti-Static	Yes		
FDA Approved	Yes		

