

# PRODUCT DATA SHEET

## U92/2 ENF G White

130200

|   |  |   |                          |
|---|--|---|--------------------------|
| Thickness (nominal)   | 1.3 mm                                       | / | 0.051 inch               |
| Weight  | 1.5 Kg/m <sup>2</sup>                        | / | 0.31 lbs/ft <sup>2</sup> |
| Maximum Width   | 3200 mm                                      | / | 126 inch                 |
| Minimum Pulley or Knife Edge Diameter<br>(With the recommended joint)<br>With the recommended joint & reverse flex,<br>Overlap joint or Fasteners | 12 mm  | / | 0.47 inch                |
|   | 35 mm  | / | 1.40 inch                |
| Load for 1% Extension   | 7 daN/cm                                     | / | 40 lbs/inch              |
| Standard Tension  | 0.5 %  |   |                          |
| Continuous Operating Temperature range  | -20° to +100° C / -4° to +212° F             |   |                          |
| Conveying Surface:  |  |   |                          |
| Material  | Polyurethane                                 |   |                          |
| Feature   | Gloss  |   |                          |
| Color   | White  |   |                          |
| Underside:  |  |   |                          |
| Material  | Non-Fray Polyester                           |   |                          |
| Feature   | PU Impregnation                              |   |                          |
| Color   | White  |   |                          |
| Co-Efficient of Friction (μ)<br>(on Steel Slide Bed/Drum)   | 0.15   |   |                          |
| Belt Construction Features  | 2 Ply Non-Fray monofilament – cover one side |   |                          |
| <b>Recommended Jointing System:</b><br>Single Finger  | <b>Alternative Splices:</b><br>Skive<br>Lace |   |                          |
| Anti-Static   | No   |   |                          |
| FDA Approved  | Yes  |   |                          |

