

# PRODUCT DATA SHEET

## U85/2ENF-AS G White

130251

Thickness (nominal)	1.3 mm	/	0.051 inch
Weight	1.5 Kg/m <sup>2</sup>	/	0.31 lbs/ft <sup>2</sup>
Maximum Width	3200 mm	/	126 inch
Minimum Pulley or Knife Edge Diameter (With the recommended joint) With the recommended joint & reverse flex, Overlap joint or Fasteners	12 mm	/	0.47 inch
	35 mm	/	1.4 inch
Load for 1% Extension	7 daN/cm	/	40 lbs/inch
Standard Tension	0.5 %		
Continuous Operating Temperature range	-30 <sup>o</sup> to +80 <sup>o</sup> C / -22 <sup>o</sup> to +176 <sup>o</sup> F		
Conveying Surface:			
Material	Polyurethane		
Feature	Gloss		
Color	White		
Underside:			
Material	Non-Fray Polyester		
Feature	PU Impregnation		
Color	White		
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.15		
Belt Construction Features	2 Ply Non-Fray monofilament – cover one side		
<b>Recommended Jointing System:</b> Single Finger	<b>Alternative Splices:</b> Skive Lace		
Anti-Static	Yes		
FDA Approved	Yes		

