



UNIVERSAL BELTING RESOURCE
 "Working Through Distribution"

1-800-928-9995
 customers@ubelting.com

PRODUCT DATA SHEET

U85/2KENF G White

130265

Thickness (nominal)	2.20 mm	/	0.086 inch
---------------------	---------	---	------------

Weight	2.5 Kg/m ²	/	0.51 lbs/ft ²
--------	-----------------------	---	--------------------------

Maximum Width	3000 mm	/	118 inch
---------------	---------	---	----------

Minimum Pulley or Knife Edge Diameter (With The Recommended Joint)	10 mm	/	0.39 inch
With The Recommended Joint & Reverse Flex Diameter Overlap joint or Fasteners	15 mm	/	0.59 inch

Load for 1% Extension	4 N/mm	/	23 lbs/inch
-----------------------	--------	---	-------------

Standard Tension	0.5 %		
------------------	-------	--	--

Continuous Operating Temperature Range (Product Temp.)	-30 ^o to +100 ^o C	/	-22 ^o to +212 ^o F
--	---	---	---

Conveying Surface:			
Material	Polyurethane, approx. 0.4mm		
Feature	Gloss		
Color	White		
Hardness	85A		

Underside:			
Material	Polyester		
Feature	Impregnated		
Color	White		
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.25		

Recommended Jointing System: Finger Splice	Alternative Splices: Finger over Finger Finger over Lap Step Splice Lace
---	--

Anti-Static	No
-------------	----

FDA Approved	Yes
--------------	-----

USDA Approved	No
---------------	----

Belt Construction Features	2 Ply Monofilament - Cover one Side with Non-Fray Fabric
----------------------------	--