

PRODUCT DATA SHEET

AM U92/2 ENF-AS M Blue

130401

| | | | |
|---|--|---|--------------------------|
| Thickness (nominal) | 1.3 mm | / | 0.051 inch |
| Weight | 1.3 Kg/m ² | / | 0.27 lbs/ft ² |
| Maximum Width | 3200 mm | / | 126 inch |
| Minimum Pulley or Knife Edge Diameter (With the recommended joint) With the recommended joint & reverse flex, Overlap joint or Fasteners | 12 mm | / | 0.47 inch |
| | 35 mm | / | 1.40 inch |
| Load for 1% Extension | 7 daN/cm | / | 40 lbs/inch |
| Standard Tension | 0.5 % | | |
| Continuous Operating Temperature range | -20° to +100° C / -4° to +212° F | | |
| Conveying Surface: | | | |
| Material | Anti-Microbial Polyurethane | | |
| Feature | Matt | | |
| Color | Blue | | |
| Underside: | | | |
| Material | Non-Fray Polyester | | |
| Feature | PU Impregnation | | |
| Color | Blue | | |
| Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum) | 0.15 | | |
| Belt Construction Features | 2 Ply Non-Fray monofilament – cover one side | | |
| Recommended Jointing System: Single Finger | Alternative Splices: Lace Skive | | |
| Anti-Static | Yes | | |
| FDA | Yes | | |

