



UNIVERSAL BELTING RESOURCE

"Working Through Distribution"

1-800-928-9995

customers@ubelting.com

PRODUCT DATA SHEET

0/2EC-0 Pet/Cotton Bare White

140200

Thickness (nominal)	2.20 mm	/	0.087 inch
---------------------	---------	---	------------

Weight	2.1 Kg/m ²	/	0.43 lbs/ft ²
--------	-----------------------	---	--------------------------

Maximum Width	2200 mm	/	86 inch
---------------	---------	---	---------

Minimum Pulley or Knife Edge Diameter (With The Recommended Joint)	15 mm	/	0.59 inch
With The Recommended Joint & Reverse Flex Diameter Overlap joint or Fasteners	15 mm	/	0.59 inch

Load for 1% Extension	4 N/mm	/	23 lbs/inch
-----------------------	--------	---	-------------

Standard Tension	0.5 %		
------------------	-------	--	--

Continuous Operating Temperature Range (Product Temp.)	-10 ⁰ to +80 ⁰ C	/	+14 ⁰ to +176 ⁰ F
--	--	---	---

Conveying Surface:			
Material	Polyester / Cotton		
Feature	Bare		
Color	Beige		
Hardness	N/A		

Intermediate Layer:			
Material	PVC		

Underside:			
Material	Polyester		
Feature	Bare		
Color	White		
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.15		

Recommended Jointing System:	Alternative Splices:
Finger Splice	Finger over Finger Finger over Lap Step Splice Lace

Anti-Static	No
-------------	----

FDA Approved	Yes
--------------	-----

USDA Approved	No
---------------	----

Belt Construction Features	2 Ply Corse Structured Polyester / Cotton Top, Polyester Bottom, Bare x Bare With PVC Inner Layer. Great For Dough Applications.
----------------------------	--