



UNIVERSAL BELTING RESOURCE
 "Working Through Distribution"

1-800-928-9995
 customers@ubelting.com

PRODUCT DATA SHEET

0/2EC-0 Pet/Cotton White

140205

Thickness (nominal)	2.50 mm	/	0.098 inch
---------------------	---------	---	------------

Weight	2.3 Kg/m ²	/	0.47 lbs/ft ²
--------	-----------------------	---	--------------------------

Maximum Width	2200 mm	/	86 inch
---------------	---------	---	---------

Minimum Pulley or Knife Edge Diameter (With The Recommended Joint)	50 mm	/	1.97 inch
With The Recommended Joint & Reverse Flex Diameter Overlap joint or Fasteners	75 mm	/	2.95 inch

Load for 1% Extension	8 N/mm	/	46 lbs/inch
-----------------------	--------	---	-------------

Standard Tension	0.5 %
------------------	-------

Continuous Operating Temperature Range (Product Temp.)	-10 ^o to +80 ^o C	/	+14 ^o to +176 ^o F
--	--	---	---

Conveying Surface:	
Material	Polyester / Cotton
Feature	Bare
Color	Beige
Hardness	N/A

Intermediate Layer:	
Material	PVC

Underside:	
Material	Polyester / Cotton
Feature	Bare
Color	Beige
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.15

Recommended Jointing System:	Alternative Splices:
Finger Splice	Finger over Finger Finger over Lap Step Splice Lace

Anti-Static	No
-------------	----

FDA Approved	Yes
--------------	-----

USDA Approved	No
---------------	----

Belt Construction Features	2 Ply Corse Structured Polyester / Cotton Bare x Bare With PVC Inner Layer. Great For Dough Applications.
----------------------------	---