



UNIVERSAL BELTING RESOURCE

"Working Through Distribution"

1-800-928-9995

customers@ubelting.com

PRODUCT DATA SHEET

U0/1EE White

140210

Thickness (nominal)	2.2 mm	/	0.087 inch
---------------------	--------	---	------------

Weight	1.5 Kg/m ²	/	0.33 lbs/ft ²
--------	-----------------------	---	--------------------------

Maximum Width	2650 mm	/	104 inch
---------------	---------	---	----------

Minimum Pulley or Knife Edge Diameter (With the recommended joint)	15 mm	/	.60 inch
With the recommended joint & reverse flex, Overlap joint or Fasteners	15 mm	/	.60 inch

Load for 1% Extension	5 daN/cm	/	29 lbs/inch
-----------------------	----------	---	-------------

Standard Tension	0.5 %
------------------	-------

Continuous Operating Temperature range	-30° to +100° C / -22° to +212° F
--	-----------------------------------

Conveying Surface:	
Material	Polyester fabric
Feature	PU impregnation
Color	White

Underside:	
Material	Polyester fabric
Feature	PU impregnation
Color	White
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.15

Belt Construction Features	1 Ply – double fabric polyester
----------------------------	---------------------------------

Recommended Jointing System: Single Finger	Alternative Spices: Lace
---	-----------------------------

Anti-Static	No
-------------	----

