



UNIVERSAL BELTING RESOURCE

"Working Through Distribution"

1-800-928-9995

customers@ubelting.com

PRODUCT DATA SHEET

0/1EC White

140300

| | | | |
|---------------------|---------|---|------------|
| Thickness (nominal) | 1.25 mm | / | 0.049 inch |
|---------------------|---------|---|------------|

| | | | |
|--------|-----------------------|---|--------------------------|
| Weight | 0.6 Kg/m ² | / | 0.14 lbs/ft ² |
|--------|-----------------------|---|--------------------------|

| | | | |
|---------------|---------|---|---------|
| Maximum Width | 2400 mm | / | 94 inch |
|---------------|---------|---|---------|

| | | | |
|--|-------|---|-----------|
| Minimum Pulley or Knife Edge Diameter (With The Recommended Joint) | 6 mm | / | 0.24 inch |
| With The Recommended Joint & Reverse Flex Diameter Overlap joint or Fasteners | 30 mm | / | 1.18 inch |

| | | | |
|-----------------------|--------|---|-------------|
| Load for 1% Extension | 2 N/mm | / | 11 lbs/inch |
|-----------------------|--------|---|-------------|

| | | | |
|------------------|-------|--|--|
| Standard Tension | 0.5 % | | |
|------------------|-------|--|--|

| | | | |
|--|--|---|---|
| Continuous Operating Temperature Range (Product Temp.) | -30 ^o to +80 ^o C | / | -22 ^o to +176 ^o F |
|--|--|---|---|

| | | | |
|--------------------|------------------|--|--|
| Conveying Surface: | | | |
| Material | Cotton Polyester | | |
| Feature | Bare | | |
| Color | White | | |
| Hardness | N/A | | |

| | | | |
|---|------------------|--|--|
| Underside: | | | |
| Material | Cotton Polyester | | |
| Feature | Impregnated | | |
| Color | White | | |
| Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum) | 0.25 | | |

| | |
|---|-----------------------------|
| Recommended Jointing System: Finger Splice | Alternative Splices: N/A |
|---|-----------------------------|

| | |
|-------------|----|
| Anti-Static | No |
|-------------|----|

| | |
|--------------|-----|
| FDA Approved | Yes |
|--------------|-----|

| | |
|---------------|----|
| USDA Approved | No |
|---------------|----|

| | |
|----------------------------|--|
| Belt Construction Features | 1 Ply Cotton Polyester - Impregnated Fabric Bottom Side. Rotary Molder Belt |
|----------------------------|--|