



UNIVERSAL BELTING RESOURCE

"Working Through Distribution"

1-800-928-9995

customers@ubelting.com

PRODUCT DATA SHEET

SI/2E-AS G White

320200

| | | | |
|---------------------|---------|---|------------|
| Thickness (nominal) | 1.60 mm | / | 0.063 inch |
|---------------------|---------|---|------------|

| | | | |
|--------|------------------------|---|--------------------------|
| Weight | 1.80 Kg/m ² | / | 0.37 lbs/ft ² |
|--------|------------------------|---|--------------------------|

| | | | |
|---------------|---------|---|----------|
| Maximum Width | 3100 mm | / | 122 inch |
|---------------|---------|---|----------|

| | | | |
|--|-------|---|-----------|
| Minimum Pulley or Knife Edge Diameter (With The Recommended Joint) | 15 mm | / | 0.59 inch |
| With The Recommended Joint & Reverse Flex Diameter Overlap joint or Fasteners | 40 mm | / | 1.57 inch |

| | | | |
|-----------------------|--------|---|-------------|
| Load for 1% Extension | 7 N/mm | / | 40 lbs/inch |
|-----------------------|--------|---|-------------|

| | | | |
|------------------|-------|--|--|
| Standard Tension | 0.5 % | | |
|------------------|-------|--|--|

| | | | |
|--|---|---|---|
| Continuous Operating Temperature Range (Product Temp.) | -30 ^o to +100 ^o C | / | -22 ^o to +212 ^o F |
|--|---|---|---|

| | | | |
|--------------------|--------------------------|--|--|
| Conveying Surface: | | | |
| Material | Silicone, approx. 0.30mm | | |
| Feature | Gloss | | |
| Color | White | | |
| Hardness | 30A | | |

| | | | |
|---|-------------|--|--|
| Underside: | | | |
| Material | Polyester | | |
| Feature | Impregnated | | |
| Color | White | | |
| Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum) | 0.17 | | |

| | |
|---|--|
| Recommended Jointing System: Finger Splice | Alternative Splices: Finger over Finger (60" Maximum Width) Lace |
|---|--|

| | |
|-------------|-----|
| Anti-Static | Yes |
|-------------|-----|

| | |
|--------------|-----|
| FDA Approved | Yes |
|--------------|-----|

| | |
|---------------|----|
| USDA Approved | No |
|---------------|----|

| | |
|----------------------------|--|
| Belt Construction Features | 2 Ply Monofilament - Cover One Side With Silicone Cover and Urethane Inner layer. Suitable for short periods to 120° C |
|----------------------------|--|