



UNIVERSAL BELTING RESOURCE
 "Working Through Distribution"

1-800-928-9995
 customers@ubelting.com

PRODUCT DATA SHEET

SI/2E-AS G Blue

320205

Thickness (nominal)	1.20 mm / 0.047 inch
---------------------	----------------------

Weight	1.50 Kg/m ² / 0.31 lbs/ft ²
--------	---

Maximum Width	2000 mm / 78.75 inch
---------------	----------------------

Minimum Pulley or Knife Edge Diameter (With The Recommended Joint)	10 mm / 0.39 inch
With The Recommended Joint & Reverse Flex Diameter Overlap joint or Fasteners	50 mm / 1.96 inch

Load for 1% Extension	9 N/mm / 51 lbs/inch
-----------------------	----------------------

Standard Tension	0.5 %
------------------	-------

Continuous Operating Temperature Range (Product Temp.)	-10 ⁰ to +80 ⁰ C / +14 ⁰ to +176 ⁰ F
--	--

Conveying Surface:	
Material	Silicone, approx. 0.15mm
Feature	Gloss
Color	Blue
Hardness	30A

Underside:	
Material	Polyester
Feature	Impregnated
Color	White
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.20

Recommended Jointing System: Finger Splice	Alternative Splices: Lace
---	------------------------------

Anti-Static	Yes
-------------	-----

FDA Approved	Yes
--------------	-----

USDA Approved	No
---------------	----

Belt Construction Features	2 Ply Monofilament - Cover One Side With Silicone Cover and Urethane Inner Layer
----------------------------	--