



**UNIVERSAL BELTING RESOURCE**  
 "Working Through Distribution"

1-800-928-9995  
 customers@ubelting.com

# PRODUCT DATA SHEET

## U97/2E-AS PP WHITE

330100

Thickness (nominal)	1.70 mm	/	0.067 inch
Weight	1.60 Kg/m <sup>2</sup>	/	0.33 lbs/ft <sup>2</sup>
Maximum Width	2000 mm	/	78.75 inch
Minimum Pulley or Knife Edge Diameter (With the recommended joint) With the recommended joint & reverse flex, Overlap joint or Fasteners	75 mm	/	2.95 inch
	150 mm	/	5.906 inch
Load for 1% Extension	6 daN/cm	/	34 lbs/inch
Standard Tension	0.5 %		
Continuous Operating Temperature range	-10 <sup>0</sup> to +70 <sup>0</sup> C / -14 <sup>0</sup> to +158 <sup>0</sup> F		
Conveying Surface:			
Material	Polypropylene		
Feature	Gloss		
Color	Clear		
Underside:			
Material	Polyester		
Feature	Bare		
Color	White		
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.15		
Belt Construction Features	2 Ply monofilament cover one side		
<b>Recommended Jointing System:</b> Single Finger	<b>Alternative Spices:</b>		
Anti-Static	Yes		
FDA Approved	Yes		

