



UNIVERSAL BELTING RESOURCE 1-800-928-9995
 "Working Through Distribution" customers@ubelting.com

PRODUCT DATA SHEET

2P80/04/0 S White

200220

Thickness (nominal)	2.0 mm	/ 0.079 inch
Weight	2.4 Kg/m ²	/ 0.49 lbs/ft ²
Maximum Width	3000 mm	/ 118 inch
Minimum Pulley or Knife Edge Diameter (With the recommended joint)	30 mm	/ 1.18 inch
With the recommended joint & reverse flex, Overlap joint or Fasteners	50 mm	/ 2.0 inch
Load for 1% Extension	8 daN/cm	/ 46 lbs/inch
Standard Tension	0.5 %	
Continuous Operating Temperature range	-10 ^o to +70 ^o C / +14 ^o to +158 ^o F	
Conveying Surface:		
Material	PVC	
Feature	Satin	
Color	White	
Underside:		
Material	Polyester	
Feature	Bare	
Color	White	
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.2 – 0.25	
Belt Construction Features	2 ply monofilament – cover one side	
Recommended Jointing System:	Alternative Splices:	
Finger Over Finger	Finger Splice Step Splice Lace	
Finger Over Lap		
Anti-Static	No	
FDA Approved	Yes	
USDA Approved	Yes	

