



**UNIVERSAL BELTING RESOURCE**

"Working Through Distribution"

1-800-928-9995

customers@ubelting.com

# PRODUCT DATA SHEET

**2P80/04/0 H M LT GN**

**200225**

Thickness (nominal)	2.0 mm	/ 0.079 inch
---------------------	--------	--------------

Weight	2.3 Kg/m <sup>2</sup>	/ 0.47 lbs/ft <sup>2</sup>
--------	-----------------------	----------------------------

Maximum Width	2000 mm	/ 78.75 inch
---------------	---------	--------------

Minimum Pulley or Knife Edge Diameter (With the recommended joint)	50 mm	/ 2.0 inch
With the recommended joint & reverse flex, Overlap joint or Fasteners	75 mm	/ 3.0 inch

Load for 1% Extension	9 daN/cm	/ 51 lbs/inch
-----------------------	----------	---------------

Standard Tension	0.5 %
------------------	-------

Continuous Operating Temperature range	-10 <sup>0</sup> to +80 <sup>0</sup> C / +14 <sup>0</sup> to +176 <sup>0</sup> F
--	--

Conveying Surface:	
Material	PVC
Feature	Matt
Color	Light Green

Underside:	
Material	Polyester
Feature	Bare
Color	Gray
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.2 – 0.25

Belt Construction Features	2 ply monofilament – cover one side
----------------------------	-------------------------------------

<b>Recommended Jointing System:</b> Finger over Finger Finger over Lap	<b>Alternative Splices:</b> Finger Splice Step Splice Lace
--	---

Anti-Static	Yes
-------------	-----

