



**UNIVERSAL BELTING RESOURCE**  
 "Working Through Distribution"

1-800-928-9995  
 customers@ubelting.com

# PRODUCT DATA SHEET

**2P80/04/0 S BL**

**200241**

Thickness (nominal)	2.0 mm	/	0.079 inch
Weight	2.5 Kg/m <sup>2</sup>	/	0.51 lbs/ft <sup>2</sup>
Maximum Width	3000 mm	/	118 inch
Minimum Pulley or Knife Edge Diameter (With the recommended joint) With the recommended joint & reverse flex, Overlap joint or Fasteners	25 mm	/	1.0 inch
	50 mm	/	2.0 inch
Load for 1% Extension	8 daN/cm	/	46 lbs/inch
Standard Tension	0.5 %		
Continuous Operating Temperature range	-10 <sup>0</sup> to +90 <sup>0</sup> C / +14 <sup>0</sup> to +194 <sup>0</sup> F		
Conveying Surface:			
Material	PVC		
Feature	Satin		
Color	Blue		
Underside:			
Material	Polyester		
Feature	Bare		
Color	White		
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.2-0.25		
Belt Construction Features	2 Ply monofilament – cover one side		
<b>Recommended Jointing System:</b>		<b>Alternative Splices:</b>	
Finger Over Finger	Finger Splice Step Splice Lace		
Finger Over Lap			
Anti-Static	No		
FDA Approved	Yes		

