



**UNIVERSAL BELTING RESOURCE**

"Working Through Distribution"

1-800-928-9995

customers@ubelting.com

# PRODUCT DATA SHEET

**3P180/30/0 S Green**

**200301**

Thickness (nominal)	6.0 mm	/ 0.236 inch
Weight	6.8 Kg/m <sup>2</sup>	/ 1.39 lbs/ft <sup>2</sup>
Maximum Width	2000 mm	/ 78.75 inch
Minimum Pulley or Knife Edge Diameter (With the recommended joint)	150 mm	/ 6.0 inch
With the recommended joint & reverse flex, Overlap joint or Fasteners	200 mm	/ 7.9 inch
Load for 1% Extension	18 daN/cm	/ 103 lbs/inch
Standard Tension	0.5 %	
Continuous Operating Temperature range	-10 <sup>o</sup> to +70 <sup>o</sup> C / +14 <sup>o</sup> to +158 <sup>o</sup> F	
Conveying Surface:		
Material	PVC	
Feature	Satin	
Color	Green	
Underside:		
Material	Polyester	
Feature	Bare	
Color	White	
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.2 - 0.25	
Belt Construction Features	3 ply monofilament – cover one side	
Recommended Jointing System:	Alternative Spices:	
Finger over Finger	Finger Splice Step Splice Lace	
Finger over Lap		
Anti-Static	Yes	

