

PRODUCT DATA SHEET

3P120/07/0 S Green

200305

| | | |
|---------------------|--------|-------------|
| Thickness (nominal) | 3.6 mm | / 0.14 inch |
|---------------------|--------|-------------|

| | | |
|--------|-----------------------|----------------------------|
| Weight | 4.1 Kg/m ² | / 0.84 lbs/ft ² |
|--------|-----------------------|----------------------------|

| | | |
|---------------|---------|------------|
| Maximum Width | 3000 mm | / 118 inch |
|---------------|---------|------------|

| | | |
|--|--------|------------|
| Minimum Pulley or Knife Edge Diameter (With the recommended joint) | 100 mm | / 4.0 inch |
| With the recommended joint & reverse flex, Overlap joint or Fasteners | 150 mm | / 6.0 inch |

| | | |
|-----------------------|-----------|---------------|
| Load for 1% Extension | 12 daN/cm | / 69 lbs/inch |
|-----------------------|-----------|---------------|

| | |
|------------------|-------|
| Standard Tension | 0.5 % |
|------------------|-------|

| | |
|--|--|
| Continuous Operating Temperature range | -10 ⁰ to +80 ⁰ C / +14 ⁰ to +176 ⁰ F |
|--|--|

| | |
|--------------------|-------|
| Conveying Surface: | |
| Material | PVC |
| Feature | Satin |
| Color | Green |

| | |
|---|------------|
| Underside: | |
| Material | Polyester |
| Feature | Bare |
| Color | White |
| Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum) | 0.2 - 0.25 |

| | |
|----------------------------|-------------------------------------|
| Belt Construction Features | 3 ply monofilament – cover one side |
|----------------------------|-------------------------------------|

| | |
|--|---|
| Recommended Jointing System: Step Splice | Alternative Splices: Finger Over Finger Finger Over Lap Finger Splice Lace |
|--|---|

| | |
|-------------|-----|
| Anti-Static | Yes |
|-------------|-----|

