



UNIVERSAL BELTING RESOURCE
 "Working Through Distribution"

1-800-928-9995
 customers@ubelting.com

PRODUCT DATA SHEET

3P150/10/01 S Green

200307

Thickness (nominal)	3.9 mm	/	0.153 inch
Weight	4.5 Kg/m ²	/	0.922 lbs/ft ²
Maximum Width	3000 mm	/	118 inch
Minimum Pulley or Knife Edge Diameter (With the recommended joint) With the recommended joint & reverse flex, Overlap joint or Fasteners	100 mm	/	3.9 inch
	150 mm	/	5.9 inch
Load for 1% Extension	12 daN/cm	/	69 lbs/inch
Standard Tension	0.5 %		
Continuous Operating Temperature range	-10 ⁰ to +80 ⁰ C / +14 ⁰ to +176 ⁰ F		
Conveying Surface:			
Material	PVC		
Feature	Satin		
Color	Green		
Underside:			
Material	Polyester		
Feature	Bare		
Color	White		
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.2		
Belt Construction Features	3 Ply monofilament – cover one side		
Recommended Jointing System: Step Splice	Alternative Splices: Finger over finger Finger Splice Lace		
Anti-Static	Yes		

