



UNIVERSAL BELTING RESOURCE
 "Working Through Distribution"

1-800-928-9995
 customers@ubelting.com

PRODUCT DATA SHEET

3P150/20/0 S Gray

200310

Thickness (nominal)	5.0 mm	/ 0.197 inch
Weight	5.8 Kg/m ²	/ 1.19 lbs/ft ²
Maximum Width	2000 mm	/ 78.75 inch
Minimum Pulley or Knife Edge Diameter (With the recommended joint) With the recommended joint & reverse flex, Overlap joint or Fasteners	100 mm	/ 3.90 inch
	150 mm	/ 5.90 inch
Load for 1% Extension	15 daN/cm	/ 85 lbs/inch
Standard Tension	0.5 %	
Continuous Operating Temperature range	-10 ⁰ to +80 ⁰ C / +14 ⁰ to +176 ⁰ F	
Conveying Surface:		
Material	PVC	
Feature	Satin	
Color	Grey	
Underside:		
Material	Polyester	
Feature	Bare	
Color	White	
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.2 – 0.25	
Belt Construction Features	3 ply monofilament – cover one side	
Recommended Jointing System: Step Splice	Alternative Splices: Finger Over Finger Finger Over Lap Finger Splice Lace	
Anti-Static	Yes	

