



**UNIVERSAL BELTING RESOURCE**

"Working Through Distribution"

1-800-928-9995

customers@ubelting.com

# PRODUCT DATA SHEET

**3P150/07/0 M White**

**200315**

Thickness (nominal)	3.7 mm	/	0.146 inch
Weight	4.3 Kg/m <sup>2</sup>	/	0.88 lbs/ft <sup>2</sup>
Maximum Width	2000 mm	/	78.75 inch
Minimum Pulley or Knife Edge Diameter (With the recommended joint) With the recommended joint & reverse flex, Overlap joint or Fasteners	80 mm	/	3.15 inch
	120 mm	/	4.72 inch
Load for 1% Extension	15 daN/cm	/	86 lbs/inch
Standard Tension	0.5 %		
Continuous Operating Temperature range	-10 <sup>0</sup> to +90 <sup>0</sup> C / +14 <sup>0</sup> to +194 <sup>0</sup> F		
Conveying Surface:			
Material	PVC		
Feature	Matt		
Color	White		
Underside:			
Material	Polyester		
Feature	Bare		
Color	White		
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.15		
Belt Construction Features	3 Ply monofilament – cover one side		
<b>Recommended Jointing System:</b> Step Splice	<b>Alternative Splices:</b> Finger Over Finger Finger Over Lap Finger Splice Lace		
Anti-Static	No		
FDA Approved	Yes		

