



UNIVERSAL BELTING RESOURCE

"Working Through Distribution"

1-800-928-9995

customers@ubelting.com

PRODUCT DATA SHEET

1PN100/04/04F Green

200410

Thickness (nominal)	2.00 mm	/	0.079 inch
Weight	2.1 Kg/m ²	/	0.43 lbs/ft ²
Maximum Width	1828 mm	/	72 inch
Minimum Pulley or Knife Edge Diameter (With the recommended joint) With the recommended joint & reverse flex, Overlap joint or Fasteners	25 mm	/	0.98 inch
	40 mm	/	1.57 inch
Load for 1% Extension	10 daN/cm	/	57 lbs/inch
Standard Tension	0.5 %		
Continuous Operating Temperature range	-10 ^o to +80 ^o C / +14 ^o to +176 ^o F		
Conveying Surface:			
Material	PVC		
Feature	Satin		
Color	Green		
Underside:			
Material	PVC		
Feature	Negative Pyramid		
Color	Green		
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.6 - 0.7		
Belt Construction Features	1 Ply Monofilament with Negative Pyramid		
Recommended Jointing System:	Alternative Splices:		
Single Finger			
Anti-Static	No		
FDA Approved	No		

