

# PRODUCT DATA SHEET

**2P80/04/04F S Blue**

**200540**

Thickness (nominal)	2.7 mm	/ 0.106 inch		
Weight	3.0 Kg/m <sup>2</sup>	/ 0.615 lbs/ft <sup>2</sup>		
Maximum Width	3000 mm	/ 118 inch		
Minimum Pulley or Knife Edge Diameter (With the recommended joint) With the recommended joint & reverse flex, Overlap joint or Fasteners	50 mm	/ 2.0 inch		
	75 mm	/ 3.0 inch		
Load for 1% Extension	8 daN/cm	/ 46 lbs/inch		
Standard Tension	0.5 %			
Continuous Operating Temperature range	-10 <sup>0</sup> to +90 <sup>0</sup> C / +14 <sup>0</sup> to +194 <sup>0</sup> F			
Conveying Surface:				
Material	PVC			
Feature	Satin			
Color	Blue			
Underside:				
Material	PVC			
Feature	Negative Pyramid			
Color	Blue			
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.5			
Belt Construction Features	2 ply monofilament – cover both sides			
<table style="width: 100%; border: none;"> <tr> <td style="width: 50%; border: none;"><b>Recommended Jointing System:</b> Finger Over Finger Finger Over Lap</td> <td style="width: 50%; border: none;"><b>Alternative Splices:</b> Finger Splice Step Splice Lace</td> </tr> </table>			<b>Recommended Jointing System:</b> Finger Over Finger Finger Over Lap	<b>Alternative Splices:</b> Finger Splice Step Splice Lace
<b>Recommended Jointing System:</b> Finger Over Finger Finger Over Lap	<b>Alternative Splices:</b> Finger Splice Step Splice Lace			
Anti-Static	No			
FDA Approved	Yes			

