



UNIVERSAL BELTING RESOURCE

"Working Through Distribution"

1-800-928-9995

customers@ubelting.com

# PRODUCT DATA SHEET

## 3P150/07/07 STR Light GN Matt

## 200600

Thickness (nominal) 3.90 mm / 0.153 inch

Weight 4.2 Kg/m<sup>2</sup> / 0.86 lbs/ft<sup>2</sup>

Maximum Width 3100 mm / 122 inch

Minimum Pulley or Knife Edge Diameter (With The Recommended Joint) 120 mm / 4.72 inch  
With The Recommended Joint & Reverse Flex Diameter 150 mm / 5.91 inch  
Overlap joint or Fasteners

Load for 1% Extension 10 N/mm / 57 lbs/inch

Standard Tension 0.5 %

Continuous Operating Temperature Range (Product Temp.) -10<sup>o</sup> to +70<sup>o</sup> C / +14<sup>o</sup> to +158<sup>o</sup> F

Conveying Surface:  
Material PVC, approx. 0.7mm  
Feature Matt  
Color Green  
Hardness 85A

Underside:  
Material PVC  
Feature STR Textured Pattern  
Color Green  
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum) 0.8 - 1.0

Recommended Jointing System: Step Splice  
Alternative Splices:  
Finger over Lap  
Finger over Finger  
Finger Splice  
Lace

Anti-Static No

FDA Approved No

USDA Approved No

Belt Construction Features 3 Ply Monofilament - Cover Both Sides