



UNIVERSAL BELTING RESOURCE
 "Working Through Distribution"

1-800-928-9995
 customers@ubelting.com

PRODUCT DATA SHEET

2PC80/0/0 White

200702

Thickness (nominal)	1.7 mm	/ 0.067 inch
Weight	1.7 Kg/m ²	/ 0.35 lbs/ft ²
Maximum Width	2000 mm	/ 78.75 inch
Minimum Pulley or Knife Edge Diameter (With the recommended joint) With the recommended joint & reverse flex, Overlap joint or Fasteners	20 mm	/ .79 inch
	40 mm	/ 1.58 inch
Load for 1% Extension	8 daN/cm	/ 46 lbs/inch
Standard Tension	0.5 %	
Continuous Operating Temperature range	-10 ⁰ to +70 ⁰ C / +14 ⁰ to +158 ⁰ F	
Conveying Surface:		
Material	Polyester Cotton	
Feature	Bare	
Color	White	
Underside:		
Material	Polyester Cotton	
Feature	Bare	
Color	White	
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.2 – 0.25	
Belt Construction Features	2 ply cotton polyester— bare x bare	
Recommended Jointing System:	Alternative Splices:	
Finger over Finger	Finger Splice Step Splice Lace	
Finger over Lap		
Anti-Static	No	
FDA Approved	Yes	

