



UNIVERSAL BELTING RESOURCE
 "Working Through Distribution"

1-800-928-9995
 customers@ubelting.com

PRODUCT DATA SHEET

2P100/GP/0 White

210125

Thickness (nominal)	2.8 mm	/ 0.110 inch
Weight	2.7 Kg/m ²	/ 0.55 lbs/ft ²
Maximum Width	2000 mm	/ 78.75 inch
Minimum Pulley or Knife Edge Diameter (With the recommended joint) With the recommended joint & reverse flex, Overlap joint or Fasteners	40 mm	/ 1.57 inch
	60 mm	/ 2.36 inch
Load for 1% Extension	8 daN/cm	/ 46 lbs/inch
Standard Tension	0.5 %	
Continuous Operating Temperature range	-10 ⁰ to +90 ⁰ C / +14 ⁰ to +194 ⁰ F	
Conveying Surface:		
Material	PVC	
Feature	Longitudinal Groove	
Color	White	
Underside:		
Material	Polyester	
Feature	Bare	
Color	White	
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.2 – 0.25	
Belt Construction Features	2 ply monofilament – cover one side longitudinal groove	
Recommended Jointing System:		
Finger Over Finger	Alternative Splices: Finger Over Lap Finger Splice Lace	
Anti-Static	No	
FDA Approved	Yes	

