



**UNIVERSAL BELTING RESOURCE**  
 "Working Through Distribution"

1-800-928-9995  
 customers@ubelting.com

# PRODUCT DATA SHEET

**2P100/RT/01 White**

**210140**

Thickness (nominal)	4.70 mm / 0.185 inch
---------------------	----------------------

Weight	4.6 Kg/m <sup>2</sup> / 0.94 lbs/ft <sup>2</sup>
--------	--

Maximum Width	2000 mm / 78.75 inch
---------------	----------------------

Minimum Pulley or Knife Edge Diameter (With The Recommended Joint)	60 mm / 2.36 inch
With The Recommended Joint & Reverse Flex Diameter Overlap joint or Fasteners	120 mm / 4.72 inch

Load for 1% Extension	10 N/mm / 57 lbs/inch
-----------------------	-----------------------

Standard Tension	0.5 %
------------------	-------

Continuous Operating Temperature Range (Product Temp.)	-10 <sup>0</sup> to +90 <sup>0</sup> C / +14 <sup>0</sup> to +194 <sup>0</sup> F
--	--

Conveying Surface:	
Material	PVC
Feature	Sign Wave Rough Top
Color	White
Hardness	55A

Underside:	
Material	Polyester
Feature	Impregnated
Color	White
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.25

Recommended Jointing System: Lap Splice	Alternative Splices: Finger over Lap Finger over Finger Finger Splice Lace
--	--

Anti-Static	No
-------------	----

FDA Approved	Yes
--------------	-----

USDA Approved	No
---------------	----

Belt Construction Features	2 Ply Monofilament - Cover One Side With Sign Wave Rough Top Profile
----------------------------	--