



UNIVERSAL BELTING RESOURCE
 "Working Through Distribution"

1-800-928-9995
 customers@ubelting.com

PRODUCT DATA SHEET

2PL100/LT/0 Green

210166

Thickness (nominal)	2.8 mm	/ 0.110 inch
---------------------	--------	--------------

Weight	3.0 Kg/m ²	/ 0.62 lbs/ft ²
--------	-----------------------	----------------------------

Maximum Width	2000 mm	/ 78.75 inch
---------------	---------	--------------

Minimum Pulley or Knife Edge Diameter (With the recommended joint)	50 mm	/ 2.0 inch
With the recommended joint & reverse flex, Overlap joint or Fasteners	80 mm	/ 3.15 inch

Load for 1% Extension	10 daN/cm	/ 57 lbs/inch
-----------------------	-----------	---------------

Standard Tension	0.5 %
------------------	-------

Continuous Operating Temperature range	-10 ⁰ to +70 ⁰ C / +14 ⁰ to +158 ⁰ F
--	--

Conveying Surface:	
Material	PVC
Feature	Lattice Top
Color	Green

Underside:	
Material	Polyester
Feature	Bare
Color	White
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.2 – 0.25

Belt Construction Features	2 ply low noise monofilament—cover one side lattice top
----------------------------	---

Recommended Jointing System: Finger over Finger	Alternative Splices: Finger over lap Finger Splice Lace
---	---

Anti-Static	Yes
-------------	-----

