

# PRODUCT DATA SHEET

## V65/2E LC White NPY

261206

Thickness (nominal)	2.20 mm	/ 0.086 inch
Weight	2.2 Kg/m <sup>2</sup>	/ 0.45 lbs/ft <sup>2</sup>
Maximum Width	1600 mm	/ 63.00 inch
Minimum Pulley or Knife Edge Diameter (With the recommended joint) With the recommended joint & reverse flex, Overlap joint or Fasteners	40 mm	/ 1.57 inch
	80 mm	/ 3.15 inch
Load for 1% Extension	8 daN/cm	/ 46 lbs/inch
Standard Tension	0.5 %	
Continuous Operating Temperature range	-10 <sup>0</sup> to +70 <sup>0</sup> C / +14 <sup>0</sup> to +158 <sup>0</sup> F	
Conveying Surface:		
Material	PVC	
Feature	Negative Pyramid	
Color	White	
Underside:		
Material	Polyester	
Feature	Impregnated	
Color	White	
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.2 – 0.25	
Belt Construction Features	2 ply monofilament – cover one side– Negative Pyramid	
<b>Recommended Jointing System:</b> Overlap	<b>Alternative Splices:</b> Finger Over Finger Lace	
Anti-Static	No	
FDA Approved	Yes	

