

# PRODUCT DATA SHEET

**0/V/2E-0 White**

**261217**

Thickness (nominal)	1.76 mm	/	0.069 inch
Weight	1.8 Kg/m <sup>2</sup>	/	0.12 lbs/ft <sup>2</sup>
Maximum Width	2000 mm	/	78.75 inch
Minimum Pulley or Knife Edge Diameter (With the recommended joint) With the recommended joint & reverse flex, Overlap joint or Fasteners	20 mm	/	0.79 inch
	20 mm	/	0.79 inch
Load for 1% Extension	8 daN/cm	/	46 lbs/inch
Standard Tension	0.5 %		
Continuous Operating Temperature range	-20 <sup>o</sup> to +80 <sup>o</sup> C / -4 <sup>o</sup> to +176 <sup>o</sup> F		
Conveying Surface:			
Material	Polyester		
Feature	Bare		
Color	White		
Underside:			
Material	Polyester		
Feature	Bare		
Color	White		
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.2–0.25		
Belt Construction Features	2 Ply monofilament – Bare x Bare		
Recommended Jointing System:	Alternative Splices:		
Finger over Finger	Finger over Lap Step Splice Lace		
Anti-Static	No		
FDA Approved	Yes		

