



UNIVERSAL BELTING RESOURCE

"Working Through Distribution"

1-800-928-9995

customers@ubelting.com

PRODUCT DATA SHEET

2P100/SG/0 GN

265201

Thickness (nominal)	4.7 mm	/	0.185 inch
Weight	3.6 Kg/m ²	/	0.74 lbs/ft ²
Maximum Width	2000 mm	/	78.75 inch
Minimum Pulley or Knife Edge Diameter (With the recommended joint) With the recommended joint & reverse flex, Overlap joint or Fasteners	60 mm	/	2.36 inch
	80 mm	/	3.15 inch
Load for 1% Extension	8 daN/cm	/	46 lbs/inch
Standard Tension	0.5 %		
Continuous Operating Temperature range	-10 ^o to +70 ^o C / +14 ^o to +158 ^o F		
Conveying Surface:			
Material	PVC		
Feature	Rough Top		
Color	Green		
Underside:			
Material	Polyester		
Feature	Impregnated		
Color	White		
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.2-0.25		
Belt Construction Features	2 Ply monofilament – cover one side Rough Top		
Recommended Jointing System:	Alternative Splices:		
Finger over Lap	Finger Splice Lap Splice Lace		
Finger over Finger			
Anti-Static	Yes		
FDA Approved	No		

