



UNIVERSAL BELTING RESOURCE
 "Working Through Distribution"

1-800-928-9995
 customers@ubelting.com

PRODUCT DATA SHEET

2P70/LR/0 Black

265202

Thickness (nominal)	2.60 mm	/	0.102 inch
Weight	2.6 Kg/m ²	/	0.53 lbs/ft ²
Maximum Width	2000 mm	/	78.75 inch
Minimum Pulley or Knife Edge Diameter (With the recommended joint) With the recommended joint & reverse flex, Overlap joint or Fasteners	40 mm	/	1.57 inch
	50 mm	/	1.97 inch
Load for 1% Extension	7 daN/cm	/	40 lbs/inch
Standard Tension	0.5 %		
Continuous Operating Temperature range	-10 ^o to +70 ^o C / +14 ^o to +158 ^o F		
Conveying Surface:			
Material	PVC		
Feature	Longitudinal Groove		
Color	Black		
Underside:			
Material	Polyester		
Feature	Impregnated		
Color	White		
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.25		
Belt Construction Features	2 Ply Monofilament—Cover One Side Longitudinal Groove		
Recommended Jointing System: Single Finger	Alternative Splices:		
Anti-Static	Yes		
FDA Approved	No		

