



UNIVERSAL BELTING RESOURCE 1-800-928-9995
 "Working Through Distribution" customers@ubelting.com

PRODUCT DATA SHEET

2P100/NPY/0 White

265206

Thickness (nominal)	2.20 mm	/ 0.086 inch															
Weight	2.2 Kg/m ²	/ 0.45 lbs/ft ²															
Maximum Width	1600 mm	/ 63.00 inch															
Minimum Pulley or Knife Edge Diameter (With the recommended joint) With the recommended joint & reverse flex, Overlap joint or Fasteners	40 mm	/ 1.57 inch															
	80 mm	/ 3.15 inch															
Load for 1% Extension	8 daN/cm	/ 46 lbs/inch															
Standard Tension	0.5 %																
Continuous Operating Temperature range	-10 ⁰ to +70 ⁰ C / +14 ⁰ to +158 ⁰ F																
<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;">Conveying Surface:</td> <td></td> <td></td> </tr> <tr> <td> Material</td> <td>PVC</td> <td></td> </tr> <tr> <td> Feature</td> <td>Negative Pyramid</td> <td></td> </tr> <tr> <td> Color</td> <td>White</td> <td></td> </tr> </table>			Conveying Surface:			Material	PVC		Feature	Negative Pyramid		Color	White				
Conveying Surface:																	
Material	PVC																
Feature	Negative Pyramid																
Color	White																
<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;">Underside:</td> <td></td> <td></td> </tr> <tr> <td> Material</td> <td>Polyester</td> <td></td> </tr> <tr> <td> Feature</td> <td>Impregnated</td> <td></td> </tr> <tr> <td> Color</td> <td>White</td> <td></td> </tr> <tr> <td> Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)</td> <td>0.2 – 0.25</td> <td></td> </tr> </table>			Underside:			Material	Polyester		Feature	Impregnated		Color	White		Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.2 – 0.25	
Underside:																	
Material	Polyester																
Feature	Impregnated																
Color	White																
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.2 – 0.25																
Belt Construction Features	2 ply monofilament – cover one side– Negative Pyramid																
<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;">Recommended Jointing System:</td> <td style="width: 50%;">Alternative Splices:</td> </tr> <tr> <td> Overlap</td> <td> Finger Over Finger Lace</td> </tr> </table>			Recommended Jointing System:	Alternative Splices:	Overlap	Finger Over Finger Lace											
Recommended Jointing System:	Alternative Splices:																
Overlap	Finger Over Finger Lace																
Anti-Static	No																
FDA Approved	Yes																

