



UNIVERSAL BELTING RESOURCE

"Working Through Distribution"

1-800-928-9995

customers@ubelting.com

PRODUCT DATA SHEET

2P100/05/0 M Black

265211

Thickness (nominal)	1.9 mm	/	0.075 inch
Weight	2.1 Kg/m ²	/	0.43 lbs/ft ²
Maximum Width	2000 mm	/	82 inch
Minimum Pulley or Knife Edge Diameter (With the recommended joint) With the recommended joint & reverse flex, Overlap joint or Fasteners	30 mm	/	1.18 inch
	50 mm	/	1.96 inch
Load for 1% Extension	8 daN/cm	/	46 lbs/inch
Standard Tension	0.5 %		
Continuous Operating Temperature range	-10 ^o to +70 ^o C / +14 ^o to +158 ^o F		
Conveying Surface:			
Material	PVC		
Feature	Matt		
Color	Black		
Underside:			
Material	Polyester		
Feature	Impregnated		
Color	Black		
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.2-0.25		
Belt Construction Features	2 Ply monofilament – cover one side		
Recommended Jointing System:	Alternative Splices:		
Finger over Lap	Finger Splice Lap Splice Lace		
Finger over Finger			
Anti-Static	Yes		
FDA Approved	No		

