



UNIVERSAL BELTING RESOURCE
 "Working Through Distribution"

1-800-928-9995
 customers@ubelting.com

PRODUCT DATA SHEET

2P80/0/0 White

265217

Thickness (nominal)	1.70 mm	/	0.067 inch
---------------------	---------	---	------------

Weight	1.8 Kg/m ²	/	0.37 lbs/ft ²
--------	-----------------------	---	--------------------------

Maximum Width	2000 mm	/	78.75 inch
---------------	---------	---	------------

Minimum Pulley or Knife Edge Diameter (With The Recommended Joint)	20 mm	/	0.79 inch
With The Recommended Joint & Reverse Flex Diameter Overlap joint or Fasteners	40 mm	/	1.57 inch

Load for 1% Extension	8 N/mm	/	45 lbs/inch
-----------------------	--------	---	-------------

Standard Tension	0.5 %
------------------	-------

Continuous Operating Temperature Range (Product Temp.)	-10 ^o to +70 ^o C	/	+14 ^o to +158 ^o F
--	--	---	---

Conveying Surface:	
Material	Polyester
Feature	Impregnated
Color	White
Hardness	N/A

Underside:	
Material	Polyester
Feature	Impregnated
Color	White
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.25

Recommended Jointing System: Finger over Finger	Alternative Splices: Finger over Lap Step Splice Finger Splice Lace
--	---

Anti-Static	No
-------------	----

FDA Approved	Yes
--------------	-----

USDA Approved	No
---------------	----

Belt Construction Features	2 Ply Monofilament - Impregnated Fabric on Both Sides
----------------------------	---