



UNIVERSAL BELTING RESOURCE
 "Working Through Distribution"

1-800-928-9995
 customers@ubelting.com

PRODUCT DATA SHEET

2P80/04/0 S BL

265220

Thickness (nominal)	2.0 mm	/ 0.079 inch
Weight	2.5 Kg/m ²	/ 0.51 lbs/ft ²
Maximum Width	2000 mm	/ 78.75 inch
Minimum Pulley or Knife Edge Diameter (With the recommended joint) With the recommended joint & reverse flex, Overlap joint or Fasteners	30 mm	/ 1.18 inch
	50 mm	/ 2.0 inch
Load for 1% Extension	8 daN/cm	/ 46 lbs/inch
Standard Tension	0.5 %	
Continuous Operating Temperature range	-10 ⁰ to +80 ⁰ C / +14 ⁰ to +176 ⁰ F	
Conveying Surface:		
Material	PVC	
Feature	Matt	
Color	Blue	
Underside:		
Material	Polyester	
Feature	Impregnated	
Color	White	
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.25	
Belt Construction Features	2 Ply monofilament – cover one side	
Recommended Jointing System: Overlap	Alternative Spices: Single Finger Finger over Lap Finger over Finger Lace	
Anti-Static	No	
FDA Approved	Yes	

