



UNIVERSAL BELTING RESOURCE
 "Working Through Distribution"

1-800-928-9995
 customers@ubelting.com

PRODUCT DATA SHEET

2P70/20/0 AS G Gray

266223

Thickness (nominal)	3.40 mm	/	0.133 inch
---------------------	---------	---	------------

Weight	4.1 Kg/m ²	/	0.84 lbs/ft ²
--------	-----------------------	---	--------------------------

Maximum Width	2000 mm	/	78.75 inch
---------------	---------	---	------------

Minimum Pulley or Knife Edge Diameter (With The Recommended Joint)	60 mm	/	2.36 inch
With The Recommended Joint & Reverse Flex Diameter Overlap joint or Fasteners	80 mm	/	3.15 inch

Load for 1% Extension	7 N/mm	/	39 lbs/inch
-----------------------	--------	---	-------------

Standard Tension	0.5 %
------------------	-------

Continuous Operating Temperature Range (Product Temp.)	-10 ^o to +70 ^o C	/	+14 ^o to +158 ^o F
--	--	---	---

Conveying Surface:	
Material	PVC, approx. 2.0mm
Feature	Gloss
Color	Gray
Hardness	35A

Underside:	
Material	Polyester
Feature	Impregnated
Color	White
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.25

Recommended Jointing System: Step Splice	Alternative Splices: Finger over Lap Finger over Finger Finger Splice Lace
---	--

Anti-Static	Yes
-------------	-----

FDA Approved	No
--------------	----

USDA Approved	No
---------------	----

Belt Construction Features	2 Ply Monofilament - Cover One Side
----------------------------	-------------------------------------