



UNIVERSAL BELTING RESOURCE
 "Working Through Distribution"

1-800-928-9995
 customers@ubelting.com

PRODUCT DATA SHEET

2P70/05/0 AS G Black

266226

Thickness (nominal)	2.10 mm / 0.082 inch
---------------------	----------------------

Weight	2.6 Kg/m ² / 0.53 lbs/ft ²
--------	--

Maximum Width	2000 mm / 78.75 inch
---------------	----------------------

Minimum Pulley or Knife Edge Diameter (With The Recommended Joint)	40 mm / 1.57 inch
With The Recommended Joint & Reverse Flex Diameter Overlap joint or Fasteners	50 mm / 1.97 inch

Load for 1% Extension	7 N/mm / 39 lbs/inch
-----------------------	----------------------

Standard Tension	0.5 %
------------------	-------

Continuous Operating Temperature Range (Product Temp.)	-10 ⁰ to +70 ⁰ C / +14 ⁰ to +158 ⁰ F
--	--

Conveying Surface:	
Material	PVC, approx. 0.5mm
Feature	Gloss
Color	Black
Hardness	75A

Underside:	
Material	Polyester
Feature	Impregnated
Color	White
Co-Efficient of Friction (μ) (on Steel Slide Bed/Drum)	0.25

Recommended Jointing System: Step Splice	Alternative Splices: Finger over Lap Finger over Finger Finger Splice Lace
---	--

Anti-Static	Yes
-------------	-----

FDA Approved	No
--------------	----

USDA Approved	No
---------------	----

Belt Construction Features	2 Ply Monofilament - Cover One Side
----------------------------	-------------------------------------